

# BELUGA™

## Open Channel Ultrasonic Digital Doppler Flow Meter Sensor



The BELUGA™ is the newest ultrasonic Doppler area/velocity flow meter sensor for open channel flow measurements from Flow-Tronic. The new sensor combines advanced digital Doppler ultrasonic velocity sensing technology with most modern and powerful DSP processor technology allowing realtime spectral analysis of the velocity distribution through the cross-sectional area.

Use the BELUGA™ in combination with the RTQ flow logger series for portable monitoring and for permanent monitoring with the IFQ Monitor or UNI-TRANS™ which display flow rate, velocity, level and much more.

## Technical Specifications

### Velocity Measurement

Method	Ultrasonic Doppler
Frequency	1 MHz
Range	-2 to +6 m/s
Accuracy	better than 1% (according to hydraulic and installation conditions compliance)
Resolution	0,001 m/s
Zero Stability	0,01 m/s

### Optional Combined Level Measurement (Ultrasonic)

Method	Ultrasonic pulsed echo
Range	0,00 to 1,75 m (with ULS-02) 0,00 to 5,75 m (with ULS-06)
Accuracy	±0,2% of reading (with ULS-06) ±0,3% of reading (with ULS-02) Includes non-linearity and hysteresis
Temp. Error	max. 0,04%/K
Resolution	1 mm

### Optional Combined Level Measurement (Radar)

Method	Radar
Range	0,01 to 15 m
Accuracy	±2 mm of reading
Resolution	1 mm

### Optional Separate Level Measurement

Method	Any 4-20 mA loop powered sensor
--------	---------------------------------

### Flow Measurement

Method	Conversion from measured velocity to average velocity based on integrated spectral analysis of the velocity distribution in the cross-sectional area. Conversion of water level and pipe size to fluid area. Multiplication of fluid area by average velocity to obtain the flow rate.
--------	---

Conversion Accuracy	±5% of reading Assumes pipe is 5 to 100% full
---------------------	--

### Communication

RS-485 communications port with Modbus ASCII slave communication protocol

### Outputs (optional)

4-20 mA	1 for validated velocity (vQP) or validated velocity including median filter (vQPMF)
---------	--

### Internal Temperature Measurement

Method	Digital sensor
Range	-40° to 80°C

## Technical Specifications

### Material & Dimensions

Enclosure	ERTACETAL®
Dimensions	190 mm L, 48 mm W, 28 mm H
Weight	0,26 kg (without the cable, level sensor and mounting accessories)
Protection rate	IP68

### Environmental Conditions

Operating temperature range	-20° to 50°C
Storage temperature range	-30° to 60°C

### Certifications

Sensor	CE
--------	----

### Sensor Cable

Material	Polyurethane jacketed
Length	Standard: 10 m Optional: 20 m, 30 m or length as needed up to 300 m

*Specifications are subject to change without notice  
Updated: October 2014*



[www.flow-tronic.com](http://www.flow-tronic.com)

Rue J.H. Cool 19a | B-4840 Welkenraedt | BELGIUM  
Tél.: +32 (0)87 899 799 | Fax: +32 (0)87 899 790  
E-mail: [info@flow-tronic.com](mailto:info@flow-tronic.com)